





## Technical sheet

# 200 ATJ

## Aerial Work Platforms Diesel Articulated Jib



Capacities	Metric
Working height	20.28 m
Horizontal outreach	12 m
Overhang	8 m
Pendular arm rotation (top/bottom)	70 ° / -70 °
Platform capacity	230 kg
Turret rotation	355 °
Platform rotation (right/left)	90 ° / 90 °
Weight and dimensions	
2.1 - Platform weight*	10050 kg
2.2 - Platform dimension (L x l)	2.1 x 0.8 m
b1 - Overall width	2.40 m
l1 - Overall length	8.42 m
l9 - Overall length (folded)	6.51 m
h17 - Overall height	2.71 m
h18 - Overall height (folded)	2.85 m
h20 - Floor height (access)	0.40 m
a7 - Counterweight offset (turret at 90°)	0.11 m
b13 - Inner turning radius	1.53 m
wa3 - Outer turning radius	4.17 m
m2 - Ground clearance at center of frame	0.44 m
y - Wheelbase	2.40 m
Performances	
Travel speed	4.70 km/h
Gradeability	40 %
Permissible leveling	5 °
Tires	
Type of tires	TyresType.SolidTyres.cured-on
Drive wheels (front/rear)	2 / 2
Steering wheels (front/rear)	2 / 2
Braking wheels (front/rear)	0 / 2
Engine	
Stage	Stage 3A
Power	45 hp / 34.10 kW
Capacity of fuel tank	78 l
Hydraulics	
Capacity of hydraulic tank	80 l
Hydraulic Flow / Hydraulic Pressure	- / 335 bar



### Equipment - Standard

20" tyres  
230V Predisposition  
4 simultaneous movements  
4 wheel drive  
4 wheel steer with crab mode  
Active oscillating front axle  
Audible alarm and illuminated indicator lamp (leveling, overload, lowering)  
Backup electrical pump  
CAN bus technology  
Dead man pedal  
Differential locking on rear axle  
Emergency stop button in platform and on frame  
Engine on swivel chair

### Equipment - Optional

110 or 230V plug with differential circuit-breaker  
Air predisposition  
Beep on every movement  
Beep upon travel  
Biodegradable oil  
Catalytic cleaner  
Coded anti-start  
Continuous turret rotation

Your dealer :



#### Siège Social

B.P. 249 - 430 rue de l'Aubinière - 44158 Ancenis Cedex - France  
Tel: 00 33 (0)2 40 09 10 11 - Fax: 00 33 (0)2 40 09 10 97  
manitou.com